











Safety Air Guns use engineered air nozzles for high performance!

Why EXAIR Safety Air Guns?

Inexpensive air guns are sold through many catalogs and industrial supply companies. Most have triggers or other parts that break quickly. Their performance is similar to open pipe, where they simply blow a lot of compressed air. In addition to the high air consumption, many produce noise levels that violate OSHA requirements. Some even generate dangerous dead end pressures that can result in serious or fatal injuries if blocked.

EXAIR's Safety Air Guns eliminate these problems. They are durable and comfortable to use. Each model uses an engineered Air Nozzle that provides superior performance by entraining large volumes of surrounding air. Safe operation is assured along with low air consumption and noise levels. Airflow that exits the nozzle can not be blocked, as required by OSHA standard 1910.242(b).

Selecting The Right Safety Air Gun

The pages that follow show four Safety Air Guns. The Precision, Soft Grip, Heavy Duty and Super Blast Safety Air Guns are available with a variety of air nozzles (listed in order of force). Stainless steel air nozzles provide more mechanical wear resistance while withstanding corrosion and high temperatures. PEEK Air Nozzles provide protection from accidental impact with the target and outstanding corrosion resistance. Air consumption, force and sound level are shown for all models. Complete details for each Air Nozzle are shown on pages 49-62.



Precision Safety Air Gun is extremely lightweight and the most comfortable to operate during periods of extended use. The small diameter nozzle and extension will fit into tight spaces while providing strong blowing force. Chip Shields for worker safety are also available.

Safety Air Guns COMPRES

Watch the video!

www.exair.com/sagvideo.htm



Soft Grip Safety Air Gun has a durable cast aluminum body that is suited for rugged industrial use. The ergonomic design has a large trigger for easy operation and a convenient hanger hook for easy storage. Chip Shields for worker safety are available. Extension Pipes and Stay Set Hoses for hard to reach areas are also available.



Heavy Duty Safety Air Gun is a powerful air gun with a durable cast aluminum body that is best suited for heavy use in rugged industrial environments. The ergonomic composite rubber grip and wide curved trigger can be used for hours without fatigue. Chip Shields for worker safety are available. Extension Pipes for hard to reach areas are also available.



Super Blast Safety Air Guns provide the strongest blowing force - ideal for long distance, wide area blowoff, cooling, and drying applications. The comfortable foam rubber handle provides a firm grip. The spring-loaded valve instantly shuts off the air supply if the air gun is dropped. Extension Pipes for hard to reach areas are also available.





Chip Shields

Protect workers from flying debris and prevent splash back!



Why the EXAIR Chip Shield?

Chip Shields are durable polycarbonate shields that protect operators from flying debris often associated with blowing chips off machined parts. Chip Shields are also great for keeping coolant from spreading everywhere during drying operations. EXAIR's Chip Shields help meet the requirements of OSHA 1910.242(b) for safe use of compressed air.

Chip Shields are available for EXAIR's Precision Safety Air Gun, Soft Grip Safety Air Gun and Heavy Duty Safety Air Gun. Chip Shields can be used on Safety Air Guns with or without an Aluminum Extension. Chip Shields are not for use on guns that use a Stay Set Hose.





Model 1360SS-CS shown

How to Order the EXAIR Chip Shield.

To order a Safety Air Gun with a Chip Shield, simply add a '-CS' to the end of the model number.

Examples:

Model 1210-CS is a Model 1210 Soft Grip Safety Air Gun with a Chip Shield.

Model 1310-12-CS is a Model 1310 Heavy Duty Safety Air Gun with a 12" (305mm) Aluminum Extension Pipe and Chip Shield.

| Chin Shiolds | for Safety Air Gun | s With Aluminium Extensions |
|--------------|--------------------|-----------------------------|
| | | |

Chip Shields are also available to be retrofitted to existing Safety Air Guns. For models that already have an Aluminum Extension in place, the Chip Shield is supplied with a rubber grommet to ensure a tight fit onto the extension.

| Chip Shield # | Safety Air Gun Models Covered |
|---------------|--|
| 901220 | 1408SS, 1408-PEEK, 1409SS, 1409-PEEK, 1410SS, 1410-PEEK |
| 901221 | 1229, 1229SS, HP1229, HP1229SS, 1280SS, 1290, 1290SS, 1296SS, 1296-PEEK, 1297SS, 1297-PEEK, 1298SS, 1298-PEEK, 1299, 1299SS, 1299-PEEK |
| 901222 | 1210, 121055, 1210-PEEK, 1230, 1230SS, HP1230, HP1230SS, 1310, 1310SS, 1310-PEEK, 1330, 1330SS, HP1330, HP1330SS |
| 901223 | 1240, 1250, 1250SS, 1250-PEEK, 1260, 1260SS, 1340, 1350, 1350SS, 1350-PEEK, 1360, 1360SS |



Model 1408SS-CS shown

Chip Shields for Safety Air Guns Without Aluminium Extensions

For models that **do not** already have an Aluminum Extension in place, a short extension nipple and the necessary adapter is provided.

| 11 | , / I I |
|------------------|--|
| Chip Shield Kit# | Safety Air Gun Models Covered |
| 901231 | 1229, 1229SS, HP1229, HP1229SS, 1280SS, 1290, 1290SS, 1296SS, 1296-PEEK, 1297SS, 1297-PEEK, 1298SS, 1298-PEEK, 1299, 1299SS, 1299-PEEK |
| 901232 | 1210, 1210SS, 1210-PEEK, 1230, 1230SS, HP1230, HP1230SS, 1310, 1310SS, 1310-PEEK, 1330, 1330SS, HP1330, HP1330SS |
| 901233 | 1240, 1250, 1250SS, 1250-PEEK, 1340, 1350, 1350SS, 1350-PEEK |
| 901234 | 1260, 1260SS, 1360, 1360SS |



Model 1299-6-CS shown





Safety Air Guns COMPRESSEDA




Precision Safety Air Gun - 1/4 NPT Inlet

EXAIR's Precision Safety Air Guns are extremely lightweight and have a focused blast of air that provides excellent cleaning capability. The small diameter nozzle and extension easily fit into tight spaces while still packing a strong punch.

The Precision Safety Air Gun is available with EXAIR's Atto, Pico and Nano Nozzles, which were engineered to maximize entrainment of ambient air while minimizing air consumption and noise. Safe operation is assured since the airflow that exits the nozzle can not be blocked, as required by OSHA standard

1910.242(b). The 58 to 75 dBA noise level is well below the limits of the OSHA maximum allowable noise exposure standard 29 CFR 1910.95(a).



polycarbonate Chip Shield.



Model 1408SS

Nozzie: 1108SS Atto Super Air Nozzie Also Available: 1408-PEEK with

1108-PEEK PEEK Plastic Atto Super Air Nozzle

| Air Consumption | | Fo | Sound Level | |
|--------------------|------|-----|----------------|-----|
| SCFM | SLPM | Ozs | Grams | dBA |
| 2.5 | 71 | 2.0 | 57 | 58 |

Model 1409SS

Nozzle: 1109SS Pico Super Air Nozzle Also Available: 1409-PEEK with

1109-PEEK PEEK Plastic Pico Super Air Nozzle

| Air Consumption | | Fo | rce* | Sound Level |
|--------------------|------|-----|-------|----------------|
| SCFM | SLPM | Ozs | Grams | dBA |
| 4.9 | 139 | 5.0 | 142 | 68 |

Model 1410SS

Nozzle: 1110SS Nano Super Air Nozzle

Also Available: 1410-PEEK with 1110-PEEK PEEK Plastic

Nano Super Air Nozzle

ption Force* Sound
Level

SLPM Ozs Grams dBA

| | SCFM | SLPM | Ozs | Grams | dBA | | |
|---|------|------|-----|-------|-----|--|--|
| | 8.3 | 235 | 8.1 | 230 | 75 | | |
| *Force measured at 12" (305mm) from target. Sound | | | | | | | |

*Force measured at 12" (305mm) from target. Sound level measured at 3' (914mm). All measurements taken at 80 PSIG (5.5 BAR).

Soft Grip Safety Air Gun - 1/4 NPT Inlet

EXAIR's Soft Grip Safety Air Gun is ideal for hours of continuous use without fatigue. The ergonomic design keeps the hand in a comfortable position and incorporates a large trigger that permits operation with one or more fingers. The durable cast aluminum body is suited for rugged industrial use and includes a convenient hanger hook for easy storage. The Soft Grip Safety Air Gun is available with Air Nozzles as shown for quiet, safe and efficient use of the compressed air supply. Aluminum Extension Pipes, Stay Set Hoses, and Chip Shields are available for most models.

Use Model 900750 Coiled Hose



| 1022ie: 1100 Super Ali NO22ie | | | | | |
|-------------------------------|------|-----|-------|----------------|-----------------------|
| A Consu | | Fo | rce* | Sound Level | Use Model |
| SCFM | SLPM | Ozs | Grams | dBA | 900750 Coiled Hose |
| 14 | 396 | 13 | 368 | 74 | Coned Hose |



The Model 1210SS uses the stainless steel Super Air Nozzle constructed of Type 316 stainless steel for rugged use and corrosion resistance.



Model 1210-PEEK SG Safety Air Gun Nozzle: 1100-PEEK Super Air Nozzle

The Model 1210-PEEK uses the PEEK Super Air Nozzle for non-marring and chemical resistance.

^{*}Force measured at 12" (305mm) from target. Sound level measured at 3' (914mm). All measurements taken at 80 PSIG (5.5 BAR).






Model 1296SS SG Safety Air Gun

Nozzle: 1108SS Stainless Steel Atto Super Air Nozzle

Also Available: 1296-PEEK with 1108-PEEK

PEEK Plastic Atto Super Air Nozzle

* Force measured at 12" (305mm) from target. Sound level measured at 3' (914mm). All measurements taken at 80 PSIG (5.5 BAR).







Model 1297SS SG Safety Air Gun

Nozzle: 1109SS Stainless Steel Pico Super Air Nozzle

Also Available: 1297-PEEK with 1109-PEEK PEEK Plastic Pico Super Air Nozzle

| Air Consumption | | Force* | | Sound Level |
|-----------------|------|--------|-------|-------------|
| SCFM | SLPM | Ozs | Grams | dBA |
| 4.9 | 139 | 5.0 | 142 | 68 |





Model 1298SS SG Safety Air Gun

Nozzle: 1110SS Stainless Steel Nano Super Air Nozzle

Also Available: 1298-PEEK with 1110-PEEK

PEEK Plastic Nano Super Air Nozzle

| Air Cons | umption | Fo | rce* | Sound Leve |
|----------|---------|-----|-------|------------|
| SCFM | SLPM | Ozs | Grams | dBA |
| 8.3 | 235 | 8.1 | 230 | 75 |





Model 1299 SG Safety Air Gun

Nozzle: 1103 Mini Super Air Nozzle

Also Available: 1299SS with 1103SS Stainless Steel Mini Super Air Nozzle 1299-PEEK with 1102-PEEK PEEK Plastic Mini Super Air Nozzle

| Air Consumption | | Fo | rce* | Sound Level |
|-----------------|------|-----|-------|-------------|
| SCFM | SLPM | Ozs | Grams | dBA |
| 10 | 283 | 9.0 | 255 | 71 |





Model 1229 SG Safety Air Gun

Nozzle: 1126 1" Flat Super Air Nozzle
Also Available: 122955 with 11265S
Stainless Steel 1" Flat Super Air Nozzle
015" (0.38mm) shim installed

| Air Consumption | | Fo | rce* | Sound Level |
|-----------------|------|-----|-------|-------------|
| SCFM | SLPM | Ozs | Grams | dBA |
| 10.5 | 297 | 9.8 | 278 | 75 |





Model 1290 SG Safety Air Gun

Nozzle: 1009 Adjustable Air Nozzle

Also Available: 1290SS with 1009SS Stainless Steel Adjustable Air Nozzle

| Air Consumption | | Fo | rce* | Sound Leve |
|-----------------|------|-----|-------|------------|
| SCFM | SLPM | Ozs | Grams | dBA |
| 13 | 368 | 12 | 340 | 79 |





Model 1280SS SG Safety Air Gun

Nozzle: 1010SS Micro Air Nozzle

| Air Cons | umption | Fo | rce* | Sound Leve |
|----------|---------|-----|-------|------------|
| SCFM | SLPM | Ozs | Grams | dBA |
| 13 | 368 | 12 | 340 | 80 |





Model HP1229 SG Safety Air Gun

Nozzle: HP1126 1" High PowerFlat Super Air Nozzle

Also Available: HP1229SS with HP1126SS

Stainless Steel 1" High PowerFlat Super Air Nozzle

.025" (0.64mm) shim installed

| Air Consu | Air Consumption | | rce* | Sound Level |
|-----------|-----------------|-----|-------|-------------|
| SCFM | SLPM | Ozs | Grams | dBA |
| 17.5 | 495 | 16 | 462 | 82 |





Model 1230 SG Safety Air Gun

Nozzle: 1122 2" Flat Super Air Nozzle
Also Available: 123055 with 1122SS
Stainless Steel 2" Flat Super Air Nozzle
3 .015" (0.38mm) shim installed

| Air Consumption | | Force* | | Sound Level |
|-----------------|------|--------|-------|-------------|
| SCFM | SLPM | Ozs | Grams | dBA |
| 22 | 622 | 22 | 624 | 77 |








SG Safety Air Gun Nozzle: 1104 3/8 NPT Super Air Nozzle Also Available: 1250SS with 1104SS 3/8 NPT Stainless Steel Super Air Nozzle 1250-PEEK with 1104-PEEK 3/8 NPT

PEEK Plastic Super Air Nozzle Model HP1230

Force measured at 12" (305mm) from target. Sound level meas at 3' (914mm). All measurements taken at 80 PSIG (5.5 BAR).





SG Safety Air Gun Nozzle: HP1125 2" High Power Flat Super Air Nozzle Also Available: HP1230SS with HP1125SS Stainless Steel 2" High Power Flat Super Air Nozzle ₩ .025" (0.64mm) shim installed

| Air Consumption | | Force* | | Sound Level |
|-----------------|-------|--------|-------|-------------|
| SCFM | SLPM | Lbs | Grams | dBA |
| 37 | 1,039 | 2.2 | 1,134 | 83 |



Model 1240 SG Safety Air Gun Nozzle: 1111-4 Super Air Nozzle Cluster

| Air Cons | Air Consumption | | Force* | | |
|----------|-----------------|-----|--------|-----|--|
| SCFM | SLPM | Lbs | Grams | dBA | |
| 56 | 1,585 | 3.2 | 1,451 | 82 | |



Model 1260 SG Safety Air Gun Nozzle: 1106 1/2 NPT Super Air Nozzle Also Available: 1260SS with 1106SS 1/2 NPT Stainless Steel Super Air Nozzle

| Air Consumption | | Fo | Force* | |
|-----------------|-------|-----|--------|-----|
| SCHM | SLPM | Lbs | Grams | dBA |
| 60 | 1,699 | 3.3 | 1,497 | 87 |



Model 1204SS-6-CS SG Back Blow Safety Air Gun Nozzle: 1004SS Stainless Steel Back Blow Air Nozzle. Aluminum Extension and Chip Shield

| Air Cons | umption | Sound Level | Use With: |
|----------|---------|-------------|---------------------------|
| SCFM | SLPM | dBA | Inside Diameter |
| 4.5 | 127 | 75 | 1/4" - 1" (6.3-25.4mm) |



Model 1206SS-6-CS SG Back Blow Safety Air Gun Nozzle: 1006SS Stainless Steel Back Blow Air Nozzle. Aluminum Extension and Chip Shield

| Air Cons | umption | Sound Level | Use With: |
|----------|---------|-------------|-------------------------|
| SCFM | SLPM | dBA | Inside Diameter |
| 22 | 622 | 80 | 7/8" - 4" (22–102mm) |

Add An Extension Pipe Or Stay Set Hose

Add an Extension Pipe or Stay Set Hose to your Soft Grip Safety Air Gun. Here's how:

- 1. Choose an EXAIR Soft Grip Safety Air Gun. Example: Model 1210
- 2. To add an Aluminum Extension Pipe, create the model number by adding a dash and number of the appropriate extension length after the model of the Soft Grip Safety Air Gun. (See table to right) Example: The Model 1210 Soft Grip Safety Air Gun with a 12" (305mm) Aluminum Extension Pipe is a Model 1210-12.
- 3. To add a Stay Set Hose, create the model number by adding a dash and number of the appropriate Stay Set Hose after the model of the Soft Grip Safety Air Gun. (Seetable to the far right) Example: The Model 1210 Safety Air Gun with a 12" (305mm) Stay Set Hose is a Model 1210-12SSH.

Aluminum Extension Pig All Soft Grip Safety Air Guns with

| Extension Pipes come fully assembled. | | | |
|---------------------------------------|--------------|--|--|
| Model Addition # | Length | | |
| -6 | 6" (152mm) | | |
| -12 | 12" (305mm) | | |
| -18 | 18" (457mm) | | |
| -24 | 24" (610mm) | | |
| -36 | 36" (914mm) | | |
| -48 | 48" (1219mm) | | |
| -60 | 60" (1524mm) | | |
| -72 | 72" (1829mm) | | |

All Soft Grip Safety Air Guns with Stay Set Hoses come fully assembled.

| , | |
|------------------|-------------|
| Model Addition # | Length |
| -6SSH | 6" (152mm) |
| -12SSH | 12" (305mm) |
| -18SSH | 18" (457mm) |
| -24SSH | 24" (610mm) |
| -30SSH | 30" (762mm) |
| -36SSH | 36" (914mm) |
| | |

Stay Set Hose not available with 1240, 1250, 1260, 1204SS and 1206SS models.



Example:

Chip Shields can be added to EXAIR's Safety Air Guns

1210 (Soft Grip Safety Air Gun) -CS (Chip Shield) 1210 -CS





Heavy Duty Safety Air Gun - 3/8 NPT Inlet

Model 1310 Heavy Duty Safety Air Gun Nozzle: 1100 Super Air Nozzle



EXAIR's Heavy Duty Safety Air Gun is a powerful air gun that delivers high force for use in rugged, industrial environments. The 3/8 NPT compressed air inlet increases the compressed air flow available to the Super Air Nozzle, resulting in higher force and flow than other air guns. The durable cast aluminum body includes an ergonomic composite rubber grip and wide curved trigger that makes it comfortable for hours of use without fatigue. Aluminum Extension Pipes and Chip Shields are available. (Stay Set Hoses are not available.)





Model 1310-PEEK HD Safety Air Gun



Nozzle: 1100SS Super Air Nozzle Type 316 Stainless Steel Super Air Nozzle for rugged use and corrosion resistance.

dRA

Nozzle: 1100-PEEK Super Air Nozzle PEEK Super Air Nozzle for nonmarring and chemical resistance.



| Air Co | nsumption | |
|--------|-----------|-----|
| SCFM | SLPM | Ozs |
| 22 | 622 | 22 |



Nozzle: 1122 2" Flat

Also Available: 1330SS with 1122SS Stainless Steel 2" Flat Super Air Nozzle ₩ .015" (0.38mm) shim installed

| AirCo | nsumption | F | orce* | Sound Level | |
|-------|-----------|-----|-------|-------------|---------------------|
| SCFM | SLPM | lbs | Grams | dBA | Use Model 900751 |
| 35 | 991 | 1.9 | 850 | 82 | Coiled Hose |

Grams

624

Model 1350 HD Safety Air Gun Nozzie: 1104 3/8 NPT Super Air Nozzle

Super Air Nozzle

Also Available: 1350SS with 1104SS 3/8 NPT Stainless Steel Super Air Nozzle 1350-PEEK with 1104-PEEK 3/8 NPT PEEK Plastic Super Air Nozzle

| Flatair pattern | |
|--------------------|-------------------|
| Model HP133 | HD Safety Air Gur |

| Air Cons | umption | Fo | Sound Level | |
|----------|---------|-----|----------------|-----|
| SCFM | SLPM | lbs | Grams | dBA |
| 37 | 1.039 | 2.2 | 1.134 | 83 |

HP1125 2" High Power Flat Super Air Nozzle

Also Available: HP1330SS with HP1125SS Stainless Steel 2" High Power Flat Super Air Nozzle ₩ .025" (0.64mm) shim installed



| Air Cons | umption | Fo | rce" | Sound Level |
|----------|---------|-----|-------|-------------|
| SCFM | SLPM | lbs | Grams | dBA |
| 56 | 1,585 | 3.2 | 1,451 | 82 |
| | | | | |

Model 1340 HD Safety Air Gun Nozzie:

1111-4 Super Air Nozzle Cluster

SCFM SLPM lbs Grams 60 1 699 87

Model 1360 HD Safety Air Gun Nozzle:

Also Available: 1360SS with 1106SS 1/2 NPT Stainless Steel Super Air Nozzle



| Air Consumption Sound Level | | Sound Level | Use With: | |
|-----------------------------|------|-------------|--------------------|--|
| SCFM | SLPM | dBA | Inside Diameter | |
| 22 | 622 | 80 | 7/8"-4" (22-102mm) | |

Model 1306SS-X-CS HD Back Blow Safety Air Gun

Nozzie:

1106 1/2 NPT

Super Air Nozzle

1006SS Stainless Steel Back Blow Air Nozzle, Aluminum Extension, and Chip Shield

*Force measured at 12" (305mm) from target. Sound level measured at 3' (914mm), All measurements taken at 80 PSIG (5.5 BAR),

Add An Extension Pipe

Add an Extension Pipe to your Heavy Duty Safety Air Gun. Here's how:

- 1. Choose an EXAIR Heavy Duty Safety Air Gun. Example: Model 1310
- 2. To add an Aluminum Extension Pipe, create the model number by adding a dash and number of the appropriate extension length afterthe model of the Heavy Duty Safety Air Gun. (See table below)

Example: The Model 1310 Heavy Duty Safety Air Gun with a 12" (305mm) Aluminum Extension Pipe is a Model 1310-12.

Aluminum Extension Pipe

All Heavy Duty Safety Air Guns with Extension Pipes come fully assembled.

| Model Addition # / Extension Length | | | |
|-------------------------------------|--------------|--|--|
| -6 | 6" (152mm) | | |
| -12 | 12" (305mm) | | |
| -18 | 18" (457mm) | | |
| -24 | 24" (610mm) | | |
| -36 | 36" (914mm) | | |
| -48 | 48" (1219mm) | | |
| -60 | 60" (1524mm) | | |
| -72 | 72" (1829mm) | | |

Chip Shields can be added to EXAIR's Safety Air Guns by adding a "-CS" to the Model#.

1310 (Heavy Duty Air Gun) + -CS (Chip Shield) See page 86 for available models 1310-CS



Back Blow Safety Air Guns COMPRESSED AIR



Back Blow Safety Air Guns - 1/4, 3/8 and 1 NPT Inlet

Back Blow Safety Air Guns are perfect for cleaning out the inside of pipe, tube, hose or channels. EXAIR's engineered back blow nozzle provides a powerful 360 degree airflow through an array of holes to remove coolant, chips or debris. Available in our Soft Grip, Heavy Duty or Super Blast version, each gun style can be outfitted with an up to 72" extension to reach far into your product and provide cleaning. Soft Grip and Heavy Duty Back Blow Safety Air Guns are outfitted with a Chip Shield to protect the operator from flying debris. Since airflow is directed back toward the operator, personal protection equipment is recommended.



The Soft Grip Back Blow Safety Air Gun provides an ergonomic design with a 1/4 NPT

| • | inlet and a full grip trigger which is ideal for hours of continuous operation without fatigue. | |
|---|---|-------------|
| | Model | Description |

| | Consumption | | Level | With: |
|--------|-------------|------|-------|-------------------------|
| Model | SCFM | SLPM | dBA | Inside Diameter |
| 1204SS | 4.5 | 127 | 75 | 1/4"-1" (6.3-25.4mm) |

| Model | Description | Model | Description |
|--------------|---------------------------------------|--------------|---------------------------------------|
| 1204SS-6-CS | Soft Grip, 6" Extension, Chip Shield | 1204SS-24-CS | Soft Grip, 24" Extension, Chip Shield |
| 1204SS-12-CS | Soft Grip, 12" Extension, Chip Shield | 1204SS-36-CS | Soft Grip, 36" Extension, Chip Shield |



The Soft Grip Back Blow Safety Air Gun provides an ergonomic design with a 1/4 NPT inlet and a full grip trigger which is ideal for hours of continuous operation without fatigue.

| | | mption | Level | With: |
|--------|------|--------|-------|-----------------------|
| Model | SCFM | SLPM | dBA | Inside Diameter |
| 1206SS | 22 | 622 | 80 | 7/8"-4" (22-102mm) |

SLPM

622 80 Inside Diameter

7/8"-4"

(22-102mm)

| | Model | Description | Model | Description |
|---|--------------|---------------------------------------|--------------|---------------------------------------|
| | 1206SS-6-CS | Soft Grip, 6" Extension, Chip Shield | 1206SS-36-CS | Soft Grip, 36" Extension, Chip Shield |
| | 1206SS-12-CS | Soft Grip, 12" Extension, Chip Shield | 1206SS-48-CS | Soft Grip, 48" Extension, Chip Shield |
| - | 1206SS-18-CS | Soft Grip, 18" Extension, Chip Shield | 1206SS-60-CS | Soft Grip, 60" Extension, Chip Shield |
| | 1206SS-24-CS | Soft Grip, 24" Extension, Chip Shield | 1206SS-72-CS | Soft Grip, 72" Extension, Chip Shield |



1006SS Stainless Steel Back Blow Air Nozzle, Aluminum Extension and Chip Shield

The Heavy Duty Back Blow Safety Air Gun has a larger rubber grip and a larger 3/8 NPT inlet upon a durable cast aluminum gun body and full grip trigger to ease fatigue.

| Model | Description | Model | Description |
|--------------|--|--------------|--|
| 1306SS-6-CS | Heavy Duty, 6" Extension, Chip Shield | 1306SS-36-CS | Heavy Duty, 36" Extension, Chip Shield |
| 1306SS-12-CS | Heavy Duty, 12" Extension, Chip Shield | 1306SS-48-CS | Heavy Duty, 48" Extension, Chip Shield |
| 1306SS-18-CS | Heavy Duty, 18" Extension, Chip Shield | 1306SS-60-CS | Heavy Duty, 60" Extension, Chip Shield |
| 130655-24-05 | Heavy Duty 24" Extension Chin Shield | 130655-72-05 | Heavy Duty 72" Extension Chin Shield |

Super Blast Back Blow Safety Air Guns provide the strongest blowing force to remove debris from the largest pipe diameters and deepest channels. These guns are sold with a 1', 3' and 6' extension, a comfortable soft grip and a spring-loaded manual valve which will shut off automatically if it is dropped.



Model 1219SS

Super Blast Back Blow Safety Air Gun

1008SS Stainless Steel Back Blow Air Nozzle and Aluminum Extension

| Dimensions Super Blast Back Blow Safety Air Gun DOWNLOAD GRANGER GRANG | 13.22" 336mm 1-13/32 36mm 1-13/ | 3.13*********************************** |
|--|--|---|
|--|--|---|

Model

130655

| Model | Description | | Air Consumption | | Sound | Use With: |
|----------|-----------------------------------|--------|--------------------|----------|-------|-----------------|
| 1219SS | Super Blast, 1' (305mm) Extension | Model | SCFM | SLPM | dBA | Inside Diameter |
| 1219SS-3 | Super Blast, 3' (1m) Extension | | | | | 2"-16" |
| 1219SS-6 | Super Blast, 6' (1.8m) Extension | 1219SS | 5/ | 57 1,614 | 89 | (51-406mm) |

Super Blast Safety Air Guns

High Force Safety Air Guns

These hand-held versions of our Super Air Nozzle Clusters and large Super Air Nozzles provide the same strong blowing force with the added convenience of a comfortable soft grip and easy to operate spring-loaded manual valve that automatically shuts off if it is dropped. The Super Blast Safety Air Guns are ideal for long distance, wide area blowoff, cooling and drying applications. All Super Blast Safety Air Guns meet OSHA noise level and pressure requirements.



Add a longer extension pipe to your Super Blast Safety Air Gun.

Create the model number by adding a dash and number of the extension pipe to the Super Blast Safety Air Gun.

Example:

The Model 1213-4 Super Blast Safety Air Gun with a 3' extension would be a Model 1213-4-3.

1213-4 (Super Blast Safety Air Gun) + -3 (3' extension)

1213-4-3

Aluminum Extension Pipe All Super Blast Safety Air Guns with Extension Pipes come fully assembled. Model Addition#/Extension Length 36" (914mm) 1213-4 3/8 NPT 72" (1829mm) 36" (914mm) 1213-7 1/2 NPT -6 72" (1829mm) 36" (914mm) -3 1213-12 72" (1829mm)

Super Blast Safety Air Gun™



Model 1213-4 3/8 NPT female Material: Nozzles - Zinc Aluminum alloy Body - Aluminum

Airflow Pattern: see Model 1111-4 on page 62.



| Air Cons | umption | For | ce* | Sound Level |
|------------|-----------------|------------|--------|----------------|
| SCFM | SLPM | lbs | Kg | dBA |
| 56 | 1,585 | 3.2 | 1.45 | 82 |
| Force meas | ured at 12" (3) | 05mm) from | target | |

Sound level measured at 3' (914mm)
All measurements taken at 80 PSIG (5.5 BAR)



Model 1213-7 1/2 NPT female

Material: Nozzles - Zinc Aluminum alloy
Body - Aluminum

Airflow Pattern: see Model 1111-7 on page 62.



| Air Consum | ption | For | Sound Level | |
|------------|-------|-----|----------------|-----|
| SCFM S | LPM | lbs | Kg | dBA |
| 98 2 | 5.7 | 85 | | |

* Force measured at 12" (305mm) from target Sound level measured at 3' (914mm) All measurements taken at 80 PSIG (5.5 BAR)



Model 1213-12 1 NPT female

Material: Nozzles - Zinc Aluminum alloy
Body - Aluminum

Airflow Pattern: see Model 1111-12 on page 62.



| Air Cons | umption | nption Force* | | |
|-----------------------|---------------|---------------|--------|-----|
| SCFM | SLPM | lbs | Kg | dBA |
| 168 4,754 9.8 4.45 89 | | | | |
| * Force measu | red at 12" (3 | 05mm) from | target | |

Sound level measured at 3' (914mm)
All measurements taken at 80 PSIG (5.5 BAR)




Super Blast Safety Air Guns

Super Blast Safety Air Gun™



Model 1214 3/4 NPT female
Material: Nozzles - Zinc Aluminum alloy
Airflow Pattern: see Model 1112 on page 60.
Model 1214S5 also available.



| Air Cons | umption | mption Force* | | |
|----------|---------|---------------|------|-----|
| SCFM | SLPM | lbs | Kg | dBA |
| 91 | 2,577 | 4.5 | 2.04 | 96 |

Force measured at 12" (305mm) from target Sound level measured at 3' (914mm) All measurements taken at 80 PSIG (5.5 BAR) OSHA 3 hour total exposure per day without hearing protection



Model 1215 1 NPT female Material: Nozzle - Zinc Aluminum alloy Airflow Pattern: see Model 1114 on page 60. Model 1215SS also available



| Air Cons | ce* | Sound Level | | | |
|---|-------|----------------|------|-----|--|
| SCFM | SLPM | lbs | Kg | dBA | |
| 135 | 3,823 | 6.6 | 3.01 | 99 | |
| Force measured at 12" (305mm) from target | | | | | |

Sound level measured at 3' (914mm) 1216 All measurements taken at 80 PSIG (5.5 BAR) 1217



The 3' extension on the Model 1215-3 Super Blast Safety Air Gun helps an operator provide maximum blow off force to remote, tight or difficult to access areas.



Model 1216 1-1/4 NPT female Material: Nozzle - Zinc Aluminum alloy Airflow Pattern: see Model 1116 on page 61.



Model 1217 1-1/4 NPT female Material: Nozzle - Zinc Aluminum alloy Airflow Pattern: see Model 1118 on page 61.



Model 1218 1-1/4 NPT female

Material: Nozzle - Zinc Aluminum alloy

| | | | | E | (AIR.com |
|-------|------|--------------|-----|-------|----------------|
| Model | | ir mption | Fo | orce* | Sound Level |
| | SCFM | SLPM | lbs | Kg | dBA |
| 1216 | 188 | 5,324 | 9.4 | 4.25 | 102 |
| 1217 | 300 | 8.495 | 15 | 6.80 | 106 |

1218 460 13.026 23 10.43 109

* Force measured at 12" (305mm) from target Sound level measured at 3' (914mm) All measurements taken at 80 PSIG (5.5 BAR)

Model 1216 OSHA 1 hour total exposure per day without hearing protection

Model 1217 and 1218 OSHA 1/2 hour total exposure per day without hearing protection

Add a longer extension pipe to your Super Blast Safety Air Gun.

Create the model number by adding a dash and number of the extension pipe to the Super Blast Safety Air Gun.

Example:

The Model 1214 Super Blast Safety Air Gun with a 3' extension would be a Model 1214-3.

1214 (Super Blast Safety Air Gun)
-3 (3' extension)

1214-3

Aluminum Extension Pipe All Super Blast Safety Air Guns with Extension Pipes come fully assembled. Model# Model Addition # / Extension Length 1214 - 3 36* (914mm) | -6 12* (1829mm

| 1214 -3 36" (914mm) -6 72" (1829mm) 12155 -3 36" (914mm) -6 72" (1829mm) 1215 -3 36" (914mm) -6 72" (1829mm) 121555 -3 36" (914mm) -6 72" (1829mm) -3 36" (914mm) -6 72" (1829mm) -6 72" (1829mm) -7 72" (1829mm) | Model# | Model Addition # / Extension Length | | | | | |
|---|--------|-------------------------------------|-------------|----|--------------|--|--|
| 1215 -3 36" (914mm) -6 72" (1829mm) 1215SS -3 36" (914mm) -6 72" (1829mm) -3 36" (914mm) -6 72" (1829mm) | 1214 | -3 | 36" (914mm) | -6 | 72" (1829mm) | | |
| 1215SS -3 36" (914mm) -6 72" (1829mm) -3 36" (914mm) -6 72" (1829mm) | 1214SS | -3 | 36" (914mm) | -6 | 72" (1829mm) | | |
| -3 36" (914mm) -6 72" (1829mm) | 1215 | -3 | 36" (914mm) | -6 | 72" (1829mm) | | |
| 1 1 1 | 1215SS | -3 | 36" (914mm) | -6 | 72" (1829mm) | | |
| B 047/044 \ 1 # P07/4000 \ | | -3 | 36" (914mm) | -6 | 72" (1829mm) | | |
| -3 36" (914mm) -6 72" (1829mm) | | -3 | 36" (914mm) | -6 | 72" (1829mm) | | |
| -3 36" (914mm) -6 72" (1829mm) | | -3 | 36" (914mm) | -6 | 72" (1829mm) | | |

